

OILVAC 200 - OILVAC 200T

Oil and chips industrial vacuum for the mechanic's workshop
Powerful, compact and mobile vacuum cleaners for mechanical use. Suitable for the extraction and recovery of liquids, oils and emulsions, whether or not it is mixed with metal chips, dust or mud.

Big sieve basket grid for the metal chips separation and collection, and special filters for very fine dust.

Liquids capacity up to 53 gallons with easy independent discharge pump. Integrated floating device.



TECHNICAL DATA		OILVAC 200	OILVAC 200T
Voltage	V - Hz	230 - 60 1~	400 - 60 3~
Power	kW	3 x 1,1*	3
Waterlift max.	in.H ₂ O	94.48	126
Air Flow max.	cfm	318	206
Filter surface	in ²	2,170	2,170
Filter type		Star	
Ø filter	in	80	80
Media, class (IEC 60335-2-69) ²		M Hydro-Oleophobe	
Liquids capacity	gal	53	53
Solids capacity	gal	8	8
Solids capacity for very fine dust metal dust	gal	2.5	2.5
Oil filter grade	µ	300	300
Ø Suction inlet	in	2	2
Floating device		Yes	Yes
Discharge system		Electric pump 28.5 gal/min	
Noise level (EN ISO 3744)	dB(A)	78	76
Dimensions	in	48x24x51 H	48x24x61 H
Weight	lbs	452	494

* HV Version available, with 3 motors with three stages 3 x 1,3 kW for application with high water lift value needed.

Standard version price	
OILVAC 200	OILVAC200-001
OILVAC 200T	OILVAC200T-001