



SILOVAC: the highest expression of DU-PUY Flexibility
 Designed for large quantities of materials and direct discharge into big-collection baskets.
 Collection capacity of 100lt.
 Material discharge with tilting flap, butterfly valves, guillotine.
 Simplified and fast BIG-BAG bagging system.
 High surface dust filter for fine dust with manual shaker.
 Mounted on wheels or fixed on the floor.
 Sturdy chassis and forklift intakes.



TECHNICAL DATA		SILOVAC 100*	SILOVAC 100T*
Voltage	V - Hz	230 - 60 1~	400 - 60 3~
Power	kW	3 x 1,1**	3
Water Lift max.	in.H ₂ O	94	126
Air Flow max.	cfm	318	206
Filter surface	in ²	3,100	
Filter type		Star	
Ø filter	in	18	
Media, class (IEC 60335-2-69) ²		Polyester - L	
Tank capacity	gal	26.5	
Ø Suction inlet	mm.	80	
Noise level (EN ISO 3744)	dB(A)	78	72
Discharge system		Butterfly valve	
Silos chassis type		Big-bag chassis	
Dimensions	in	55x50x116 H	55x50x124 H

Standard version price	
SILOVAC 100	SILOVAC100-001
SILOVAC 100T	SILOVAC100T-001

Special version price	
SILOVAC 100 Wall mounted	
SILOVAC 100T Wall mounted	
SILOVAC 100 For discharging on the floor	
SILOVAC 100T For discharging on the floor	