

SILOVAC 600 - SILOVAC 600 AF - SILOVAC 600HV



SILOVAC: the highest expression of DU-PUY Flexibility
 Designed for large quantities of materials and direct discharge into big-collection baskets.
 Collection capacity of 159 gallon with maximum level detector.
 Material discharge with tilting flap, butterfly valves, guillotine.
 Discharge into big-bags or big-collection baskets.
 High surface dust filter for fine dust with automatic shaker and compressor.
 Mounted on telescopic chassis for easy transport.
 Sturdy chassis and forklift intakes.

TECHNICAL DATA		SILOVAC 600	SILOVAC 600AF	SILOVAC 600HV
Voltage	V - Hz	400 - 60 3~	400 - 60 3~	400 - 60 3~
Power	kW	12,5	18,5	20
Water Lift max.	in.H ₂ O	173	173	236
Continuous Waterlift	in.H ₂ O	114	126	177
Air Flow max.	cfm	6.5	8	6.5
Filter surface	in ²	10,850		
Filter type		Star		
Ø filter	in	22		
Media, class (IEC 60335-2-69) ²		M PTFE ANT		
Cleaning system		Automatic self clean with included compressor		
Safety filter		Cartridge H14 52.000 cm ²		
Tank capacity	gal	159		
Level detector		Rotary level detector		
Ø Suction inlet	in	4		
Noise level (EN ISO 3744)	dB(A)	76	81	79
Discharge system		Manual butterfly valve		
Silos chassis type		Telescopic big-bag chassis		
Dimensions	in	Low position 55x49x98 H - Highest position 55x49x157 H		
Weight	lbs	1,389	1,411	1,631

Standard version price		
SILOVAC 600		SILOVAC600-001
SILOVAC 600AF		SILOVAC600AF-001
SILOVAC 600HV		SILOVAC600HV-001
Optional		
Remote Control		RC

