

OILVAC 60 - OILVAC 100 - OILVAC 100 PUMP

Included oil & chips Kit



Oil and chips recovery industrial vacuum for mechanic workshop

Powerful single-phase industrial vacuum cleaner. They meet the requirements of extraction and recovery of liquids, oils and emulsions, whether or not mixed with metal chips, dust or mud.

Big sieve basket grid for the metal chips separation and collection, and special filters for very fine dust.

Liquids capacity up to 26 gallons with easy independent discharge pump. Integrated floating device.

TECHNICAL DATA		OILVAC 100	OILVAC 100 P
Voltage	V - Hz	230 - 60 1~	
Power	kW	2 x 1,1	
Waterlift max.	in .H ₂ O	94.48	
Air Flow max.	cfm	211	
Filter surface	in ²	186	
Filter type		Bag	
Ø filter	in	16	
Media, class (IEC 60335-2-69) ²		Polypropylene 100 micron	
Liquids capacity	Gallon	24	
Solids capacity	Gallon	8	
Solids capacity for very fine dust metal dust	Gallon	Optional	2.5
Oil filter grade	µ	Optional	300
Ø Suction inlet	in	2	
Floating device		Yes Electric	
Discharge system		Ball Valve	Electric pump 100 g/min
Noise level (EN ISO 3744)	dB(A)	77	77
Dimensions	in	29x23x49 H	
Weight	lbs	132	143

Standard version price	
OILVAC 100	OILVAC100-001
OILVAC 100 PUMP	OILVAC100PUMP-001

Optionals	
OILVAC 100 P - PPL 100 Micron filter	FI.0450.0000

Recommended accessory	
OILVAC 100/100 P - Recommended accessory Ø50	TA.0837.0000

